

## Knipex 98 03 12. Socket wrench with screwdriver handle, burnished, insulated, key width 12 mm, 237 mm

Item no. WL62205

Manufacturer Knipex

Socket wrench with screwdriver handle, burnished, insulated, key width 12 mm, 237 mm

### TECHNICAL DATA

Weight

0.1 kg



### STANDARDS & COMPLIANCE

EN 60900 IEC 60900

### DESCRIPTION

### OTHER VERSIONS

| item number             | wrench width | tool length   |
|-------------------------|--------------|---------------|
| <a href="#">WL62196</a> | 4 mm         | 230 mm        |
| <a href="#">WL62197</a> | 5 mm         | 230 mm        |
| <a href="#">WL62198</a> | 5.5 mm       | 232 mm        |
| <a href="#">WL62199</a> | 6 mm         | 232 mm        |
| <a href="#">WL62200</a> | 7 mm         | 237 mm        |
| <a href="#">WL62201</a> | 8 mm         | 237 mm        |
| <a href="#">WL62202</a> | 9 mm         | 237 mm        |
| <a href="#">WL62203</a> | 10 mm        | 237 mm        |
| <a href="#">WL62204</a> | 11 mm        | 237 mm        |
| <b>WL62205</b>          | <b>12 mm</b> | <b>237 mm</b> |
| <a href="#">WL62206</a> | 13 mm        | 237 mm        |

Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Width across flats S: 12.0mm - Handle length max.: 112mm - Head diameter d: 20mm Blade length 125mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

## PRODUCT DETAILS

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| item number                       | WL62205                                             |
| model                             | 98 03 12                                            |
| manufacturer                      | KNIPEX                                              |
| manufacturer item number          | 98 03 12                                            |
| dimensions (LxWxH)                | 235 mm x 35 mm x 32 mm                              |
| dimensions with packaging (LxWxH) | 325 mm x 124 mm x 86 mm                             |
| Packaging volume                  | 3.466 dm <sup>3</sup>                               |
| order unit                        | piece                                               |
| type of packaging                 | single pack                                         |
| standards                         | DIN EN 60900   IEC 60900                            |
| RoHS conform                      | no                                                  |
| surface                           | burnished                                           |
| ESD safe                          | no                                                  |
| VDE                               | yes                                                 |
| tool length                       | 237 mm                                              |
| type of handle                    | VDE   insulating multi-component handle, VDE-tested |
| blade length                      | 125 mm                                              |
| wrench width                      | 12 mm                                               |