

Lindström RX8140M2. Ergo precision side cutters ESD, hardened, oval head, high cutting capacity, S

Item no. WL70890

Manufacturer Lindström

ERGO precision side cutters ESD, hardened, oval head, high cutting capacity, S

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

OTHER VERSIONS

item number	Cutting edge design	Jaw shape	Cutting capacity side cutter
WL70890	with bevel	oval	0,2 - 0,5 mm
WL70891	with bevel	oval	0,2 - 0,8 mm
WL70892	with bevel	oval	0,3 - 0,8 mm

- ERGO™ precision side cutter with oval head.
- Suitable for cutting hard wires, pins, conducting wire and multi-core cables
- ESD-safe ergonomic 2-component handles
- Cutting forms: Micro-bevel (with bevel), flush (small bevel) & ultra-flush (without bevel)
- Cutting capacity specification refers to copper
- Cutting capacity: 0.1 mm to 0.8 mm and 0.4 mm to 2 mm respectively
- Material: high performance steel alloy
- Phosphated
- Precision ground cutting edges for extra long life and a clean cut
- Induction hardened cutting edges with a high degree of hardness (63-65 HRC)

- Friction-reducing screw connection for smooth cuts without overlapping of the legs
- ESD-safe handles with soft surface and firm core
- Opening spring with three different settings for spring tension and opening width
- Ideal for working on cable harnesses and printed circuit boards

PRODUCT DETAILS

item number	WL70890
manufacturer	LINDSTRÖM
manufacturer item number	RX8140M2
dimensions (LxWxH)	270 mm x 180 mm x 90 mm
order unit	piece
ESD safe	yes
Cutting edge design	with bevel
Cutting capacity side cutter	0,2 - 0,5 mm
Jaw shape	oval
tool length	135.5 mm
type of side cutter	side cutter