

DESCO 237225. Conductive Hi-Temp PCB Rack, 140mmx465mm

Réf. article DESCO 237225 **Fabricant** Desco**Réf. fabricant** DESCO 237225

DESCO 237225. Conductive Hi-Temp PCB Rack, 140mm x 465mm

DONNÉES TECHNIQUES

Authenticité de l'article	Produit original
Estado del artículo	Nuevo
Numéro de tarif douanier	39231090
Poids	0.3822 kg
Version	TEC



NORMES & CONFORMITÉ

Sécurité ESD EN 61340-5-1

DESCRIPTION

- Moulded from a static dissipative thermoplastic compound based on polypropylene copolymer with carbon black and reinforced with mica flake.
- Designed to protect CMOS loaded boards in storage.
- Recommended maximum operating temperature is 135°C.
- Open carrying handles.
- Measurements: 140mm x 465mm.
- Weight: 0.4kg.
- 25 slots with easy-to-load angle: 3mm x 8mm on a 12mm pitch

"Tools intended for use within the EPA [ESD protected area] shall, as far as is practicable, be so constructed that they do not generate or hold an electrostatic charge

All tools and machinery, for example electrical, mechanical or pneumatic, shall be so constructed that any non-insulating part of the tool or machine which may touch an ESDS [ESD sensitive items] shall be at EPA ground potential." [EN 61340-5-1 clause 5.2.10 Tools, machinery, dispensers and test equipment]

Technical information

- [237225](#) - Conductive PCB Rack, 140mm x 465mm, High Temperature