

# Product data sheet



Storeroom trolleys

## Construction:

Welded tubular and sectional steel, powder coated. 2 shelves made of derived timber material boards in angle steel frame, 12 mm high skirting. At the face ends wooden steps lifting automatically when released and standing firmly on the floor when under load, whereby the trolley is automatically locked. You can hold onto or lean against the safety handle provided. Steps can be tilted when in rest position. 2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys). Capacity upper and middle shelves 80 kg.



## Technical details:

|                              |                                |
|------------------------------|--------------------------------|
| <b>Capacity</b>              | 250 kg                         |
| <b>Shelve heights</b>        | 200, 820 mm                    |
| <b>Platform size</b>         | 1000 x 600 L x W mm            |
| <b>Outside dimension</b>     | 1322 x 611 x 1155 L x W x H mm |
| <b>Wheels</b>                | TPE 125 x 32 mm                |
| <b>net weight</b>            | 47 kg                          |
| <b>Country of origin</b>     | Germany                        |
| <b>Customs tariff number</b> | 8716800000                     |
| <b>Warranty</b>              | 10 years                       |
| <b>EAN-Code</b>              | 4017976021058                  |
| <b>Order number</b>          | 2105                           |