

Product data sheet



Pallet dollies as tugger train

Construction:

For pallets and lattice boxes in European standard sizes. Easy loading and unloading from the side with forklift. Sturdy sectional steel construction with 4 catch corners for stacking. Powder coated blue RAL 5007. 2 swivel and 2 fixed-wheel castors, with robust steel carriages suitable for tugger trains, wheels with PU tyres on aluminium rims, hubs with precision ball bearings. Swivel castors with wheel locks. Tyres are non-marking (trackless). Low-noise running on even flooring. Capacity 1000 kg. This coupling system guarantees the best possible directional stability. Tractors must have front wheel steering and tugger train drawbar! Max. 5 pallet dollies per train. Max. train speed 6 km/h. Max. train weight 3000 kg. Self-securing flat steel drawbar on the fixed-wheel side. Drawbar eye Ø 26.5 mm. Comfortable foot operation. Automatically rebounds into vertical resting position by means of gas spring. On the swivel wheel side there is a strong coupling pin Ø 25 mm with loading jaws and automatic



Technical details:

Capacity	1000 kg
loading height	290 mm
Platform size	1210 x 810 L x W mm
Outside dimension	1327 x 855 x 783 L x W x H mm
Wheels	Polyurethane 200 x 50 mm
net weight	50 kg
Country of origin	Germany
Customs tariff number	8716800000
Warranty	3 years
EAN-Code	4017976226019
Order number	22601