

# Product data sheet



Box carts 750 kg

## Construction:

Shelved trolley in angle steel construction with tubular handlebar. Ends, 1 side and top fitted with wire lattice 40 x 40 x 4 mm, completely welded and powder-coated. With 2-leaf door of angle steel with welded wire lattice on open side. 1 fixed and 4 detachable wood material shelves, surface beech grain. 2 swivel and 2 fixed-wheel castors with TPE tyres (thermoplastic elastomer), hubs with precision deep groove ball bearing. Maximum comfort: Very lowstarting, rolling and swivelling esistance. Low noise operation on level floors. Tyres are non-marking (trackless). TOTALSTOP central braking system standard on swivel castors. Clearance between shelves 280 mm. Capacity per shelf 90 kg.



## Technical details:

|                              |                                |
|------------------------------|--------------------------------|
| <b>Capacity</b>              | 750 kg                         |
| <b>Shelve heights</b>        | 292, 582, 882, 1182, 1482 mm   |
| <b>Platform size</b>         | 1000 x 680 L x W mm            |
| <b>Outside dimension</b>     | 1170 x 745 x 1792 L x W x H mm |
| <b>Wheels</b>                | TPE 200 x 40 mm                |
| <b>net weight</b>            | 144 kg                         |
| <b>Country of origin</b>     | Germany                        |
| <b>Customs tariff number</b> | 8716800000                     |
| <b>Warranty</b>              | 10 years                       |
| <b>EAN-Code</b>              | 4017976013176                  |
| <b>Order number</b>          | 5392                           |