

# Product data sheet



ESD storage trolleys

## Construction:

Electric static discharge construction (ESD = Electrostatic Discharge). Tubular steel and sectional steel welded, conductive powder coating, slate grey RAL 7015. . 2 swivel and 2 fixed-wheel castors. Wheels electrically conductive (anti-static) with TPE-ESD tyres (thermoplastic elastomer). Hubs with precision deep groove ball bearing. Maximum comfort: Very low starting, rolling and swivelling resistance. Low noise operation on level floors. Tyres are non-marking. 2 swivel castors with wheel lock, according to the European Standard EN 1757-3 (safety of platform trolleys). With 3 electrically conductive (anti-static) HPL composite shelves, rim 7 mm high. Capacity upper and middle shelves 50 kg.



## Technical details:

<b>Capacity</b>	200 kg
<b>Loading height</b>	216, 671, 1171 mm
<b>Platform size</b>	605 x 405 L x W mm
<b>Outside dimension</b>	821 x 455 x 1178 L x W x H mm
<b>Wheels</b>	TPE-ESD 125 x 32 mm
<b>net weight</b>	33 kg
<b>Country of origin</b>	Germany
<b>Customs tariff number</b>	8716800000
<b>Warranty</b>	10 years
<b>EAN-Code</b>	4017976929019
<b>Order number</b>	92901