

# Product data sheet



ESD shelved trolleys

## Construction:

Electric static discharge construction (ESD = Electrostatic Discharge). Tubular steel and sectional steel welded, conductive powder coating, slate grey. Screw and plug type construction. 1 fix and 4 variable shelves. HPL composite shelves according to DIN 68765, light grey. 2 swivel and 2 fixed-wheel castors. Wheels electrically conductive (anti-static) with TPE-ESD tyres (thermoplastic elastomer). Hubs with precision deep groove ball bearing. Maximum comfort: Very low starting, rolling and swivelling resistance. Low noise operation on level floors. Tyres are non-marking. Castors with wheel lock, according to the European Standard EN 1757-3 (safety of platform trolleys). Capacity per shelf 50 kg.



## Technical details:

<b>Capacity</b>	600 kg
<b>Shelve heights</b>	276, 576, 876, 1176, 1476 mm
<b>Platform size</b>	1000 x 600 L x W mm
<b>Outside dimension</b>	1169 x 609 x 1800 L x W x H mm
<b>Wheels</b>	TPE-ESD 200 x 40 mm
<b>net weight</b>	75 kg
<b>Country of origin</b>	Germany
<b>Customs tariff number</b>	8716800000
<b>Warranty</b>	10 years
<b>EAN-Code</b>	4017976093413
<b>Order number</b>	9341